



DVB-S/S2/S2X FHD Hybrid STB

model# DSD9615 DVB-S/S2/S2X FHD HEVC STB with various CA and Huon UI




Bringing the future to a home near you

Hardware

Processor Info	FHD 7000 DMIPS Dual 64bit A53 Secure Soc with Mali450 MP2 and HDR
Memory DDR	512MB DDR3 (2 * 256MB)
Memory NOR Flash	4MB NOR Flash
Memory NAND flash	512MB Nand TSOP Flash
Front End	DVB-S/S2/S2X, Ethernet
HDMI Output Resolution	480i, 576i, 720p@50, 720p@60/59.94, 1080i@60/59.94, 1080p@25, 1080p@30/29.97, 1080p@50, 1080p@60/59.94
LNB power load	200mA MAX
Housing Buttons	5 buttons (top side)
Housing LED	Bi color Green/Red
Dimen w*h*d (mm)	125 -30 -125
Certificates	National Certificate - CE(EU), National Certificate - CoC/ErP(EU), Optional WEEE certificate, REACH Compliant, RoHS Compliant
Lifetime	5 years at 40 degrees Celcius
Operating humidity	10 to 95% RH non-condensing
Operating temp.	0 to 40° C

Software

Browser	HTML5/HbbTV compliant browser
Software features	Language settings, Menu Bar: access to existing functionalities, Parental control, VoD support
Playback source	Web, USB Drive, UPnP
IP Streaming	HLS, MPEG-DASH, Smooth Streaming, UDP unicast, UDP multicast, RTP unicast, RTP multicast
Audio codecs	AAC, AAC-HE, AAC-HE V2 Downmix, AAC-HE V2 Passthrough, Dolby Digital / AC3 Passthrough, MP2, PCM, Wave
Video codecs	MPEG-1MPEG-1 MP/HL up to 1080P@60fps, MPEG-2 MP/HL up to 1080P@60fps, H.263, MPEG-4 AVC / H.264 HP@L4.1 MP@L4.1, HEVC Main 10 profile Level 4.x (FHD), VP8 Simple/Enhance Profile up to 1080P@30fps
Container formats	MKV, TS, MPG, AVI, FLV, 3GP, MP4, TRP, MOV, VOB, ASF, WAV
Image codecs	JPG, PNG, GIF(Up to 1280x720), BMP
Menu languages	All common languages included.
CAS (Conditional Access System)	Various CA options available
DRM	HDCP, Various DRM's supported, MS PlayReady 3.x
EPG Style	Grid style
User Interface	HUON UI



Connectivity

Connectors	DC connector, 3.5mm AV socket output, HDMI Output v2.0, S/PDIF optical or RCA output, Ethernet (RJ45 without LED)
Connectors RF (+shielding)	RF input 1 F-Type, CAN shielding 2 connectors
Connectors USB	1 * USB 2.0 - internal, 1 * USB 2.0 - side, 1 * USB 3.0 - side
WiFi/BT	Build in PCIe BT4.2+Wifi 2x2 802.11 ac 2.4G/5G with internal antenna

Accessories

Cables	3.5mm to 3RCA 1.5m, HDMI 1.2 Cable 1.5m with CEC
User Information (Manual)	Quick Start Guide
Power supply	15.6W PSU EU
Power Supply_Rating	12v 1.3A
RCU (Remote Control Unit)	ACCESS RCU (46 keys)

This product leaflet contains various optional features. Contact our sales team for a detailed quotation.

ABOUT US: EKT is a world-class design centre, specialising in Set Top Box, Modem and Smart TV designs solutions. more info? www.EKT-Digital.com

All information is non-binding and subject to change at any time

Generated 27-09-2023

EKT Shenzhen Ltd
 3rd Fl, No. 3 Bld, Qianhai L Ind Park, 63 YuanShan Rd, Qianhai, Nanshan, Shenzhen, China
 Info@EKT-Digital.com
 Tel: +86 755 26898816

EKT Germany
 Neckartal 154/1
 78628 Rottweil
 Germany
 Tel: +49 741 94227480
 solidTV@EKT-Digital.com

EKT Netherlands
 Assendorperdijk 1
 8012 EG Zwolle
 The Netherlands
 SalesEU@EKT-Digital.com

EKT LATAM
 Florida
 USA
 SalesLATAM@ekt-digital.com